



Update : 05/05/06

SUB MICRO MICRO MINI HP & CL STANDARD HEAVY DUTY SAIL WINCH SAT T.O.C Low Profile & Landing Gear retract MENU

SUB-MICRO SERIES



Model	STD	BB	Size (L x W x H) mm/in	Weight		4.8V			6V		
	US MRPS			g	oz	Speed (sec/60°)	Torque		Speed (sec/60°)	Torque	
							kg-cm	oz-in		kg-cm	oz-in
PICO	v		22.8x9.5x16.5 0.90x0.37x0.61	5.40	0.19	0.12	0.70	10	0.09	0.84	12
PICO+ F		v	22.8x9.5x19.8 0.90x0.37x0.78	6.20	0.22	0.12	0.79	11	0.10	0.90	12
NARO	v		22.0x11.24x21.35 0.87x0.44x0.84	8.80	0.31	0.11	0.80	11	0.09	1.00	14
NARO HP	v	v	22.0x11.24x21.35 0.87x0.44x0.84	8.80	0.31	0.10	1.20	16	0.09	1.40	19
NARO+F HP		v	22.2x11.0x24.95 0.87x0.43x0.98	10.00	0.35	0.10	1.70	24	not recommend at 6V under heavy loading		
NARO PRO	v		27.0x12.7x24.65 1.06x0.50x0.88	13.00	0.46	0.12	1.60	22			
NARO MAX		v	27.0x12.7x26.65 1.06x0.50x0.97	14.00	0.49	0.15	1.80	25			

STD = Teflon Bushing BB = 1 Ball Bearing
© GWS Grand Wing Servo-Tech Co., Ltd., All Rights Reserved.