ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	NOTES
1	50-00396	Connector, stereo plug, 3.5xL20.5 mm, brass, nickel plated, molding style	2	
2	30-00177	Wire, 2C BC, 28 AWG, 300V, 80C, 3.8 mm, foil + shield, PVC	1	
3	24-00028	Overmold, PVC	2	black





Wiring Diagram		
50-00396	wire color	50-00396
A	red	A
B	white	B
C	shield	C

Notes:
Functionally equivalent components may be substituted

Revision:	Date:	Description:
A	3/22/2016	Initial release
A1	7/15/2016	Modified collar exposure
A2	10/20/2016	Modified dimensions

Prepared: GL Digitally signed by GL Date: 2017.02.28 13:59:33 -08'00'

Verified: DN Digitally signed by DN Date: 2017.02.28 14:00:48 -08'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:
RoHS and REACH compliant

Function test: no open, no short circuit, no intermittent

Description:
Cable, 915 mm, 3.5 mm 3C 50-00396 audio plug to same, 28 AWG, 30-00177 wire

TENSILITY
tel 1.541.323.3228 800 877.670.7118
fax 1.541.323.4202 web tensility.com

Size: A
Part number: 10-02152
Scale: 1:1
Sheet 1 of 1

5 4 3 2 1