



- NOTES
- 1 THE RECOMMENDED TIGHTENING TORQUE OF REF. NO. ④: 0.9 TO 1 N · m.
 THE RECOMMENDED ADHESIVE AND PRIMER OF REF. NO. ④: LOCTITE 243 AND LOCK PRIMER 7649 MADE BY HENKEL JAPAN LTD.
 - 2 THE RECOMMENDED TIGHTENING TORQUE OF REF. NO. ⑫: 0.9 TO 1 N · m.
 THE RECOMMENDED ADHESIVE AND PRIMER OF REF. NO. ⑫: LOCTITE 243 AND LOCK PRIMER 7649 MADE BY HENKEL JAPAN LTD.
 - 3 ROTATION EXAMPLE ARE SHOWN FOR REF. NO. ①, ④, ⑨, AND ⑫.
 - 4 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFER, DEPENDING ON THE CABLE STRUCTURE.
 PLEASE CONFIRM BEFORE THE USE.

5	STAINLESS STEEL		12	POLYPHENYLENE SULFIDE	(BLACK) UL94V-0			
4	ZINC ALLOY	NICKEL PLATING	11	POLYAMIDE	(WHITE) UL94V-0			
3	ZINC ALLOY	NICKEL PLATING	10	HYDROGENATION ACRYLONITRILE BUTADIENE RUBBER	(BLACK)			
2	PHOSPHOR BRONZE	CONTACT AREA :GOLD 0.2#m min. TERMINAL AREA:GOLD 0.03#m min. UNDER PLATING:NICKEL 2#m min.	9	POLYAMIDE	(BLACK) UL94V-0			
			8	ACRYLONITRILE BUTADIENE RUBBER	(BLACK)			
			7	ACRYLONITRILE BUTADIENE RUBBER	(BLACK)			
1	POLYPHENYLENE SULFIDE	(BLACK) UL94V-0	6	PHOSPHOR BRONZE	NICKEL PLATING			
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS			
UNITS mm			SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
HIROSE ELECTRIC CO., LTD.			APPROVED :HY. KOBAYASHI	18.02.26	DRAWING NO.	EDC-117789-31-00		
			CHECKED :HY. KOBAYASHI	18.02.26	PART NO.	HR08D-12WLPM-10S(31)		
			DESIGNED :DS. MATSUNE	18.02.24	CODE NO.	CL108-0276-0-31		
			DRAWN :AI. NISHIYAMA	18.02.22				