


## Specification Sheet

Part Number: T18R6M4



Standard Cable Tie, 4" Long, UL Rated, 18lb Tensile Strength, PA66, Blue, 1000/pkg

Article Number	111-01845
Type	T18R
Color	Blue (BU)
Features & Benefits	<ul style="list-style-type: none"><li>• Inside serrations allow for strong hold on cables and wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force.</li><li>• Bent tail ensures a quick and simple installation.</li></ul>
Quantity Per	bag

### Product Description

T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Standard Cable Tie, 4" Long, UL Rated, 18lb Tensile Strength, PA66, Blue, 1000/pkg
<b>Global Part Name</b>	T18R-PA66-BU
<b>Minimum Tensile Strength (Imperial)</b>	18.0
<b>Minimum Tensile Strength (Metric)</b>	80.0
<b>Length L (Imperial)</b>	4.0
<b>Length L (Metric)</b>	100.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.10
<b>Width W (Metric)</b>	2.5
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	0.87
<b>Bundle Diameter Max (Metric)</b>	22.0

<b>Thickness T (Metric)</b>	1.0
-----------------------------	-----

**Height H (Metric)** 3.7

<b>Material</b>	Polyamide 6.6 (PA66)
-----------------	----------------------

**Material Shortcut** PA66

<b>US MIL SPEC</b>	MS3367-4-6
--------------------	------------

SAE-AS33671

**Flammability**

UL 94 V2

**Halogen free**

Yes

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**ROHS Complaint**

Yes

**Certification/Specification WEB**

CAGE Code 53421

**UL Recognized (US)**

Yes

**UL Listed (US and Canada)**

Yes

**UL Recognized (US and Canada)**

Yes

<b>Package Quantity(Imperial)</b>	1000
-----------------------------------	------

**Package Quantity (Metric)**

1000

**Customs Number**

3926909987