



NOTE FOR LEAD FREE CONVERSION:  
 THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO ROHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC". CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH LEAD.

- NOTES:
- MATERIALS:  
 INSULATOR IS GLASS FILLED LCP (LIQUID CRYSTAL POLYMER), U.L. 94 V-0, COLOR: BLACK; TERMINALS ARE A PHOSPHOR BRONZE ALLOY, .012" THICK.
  - TERMINAL PLATING:  
 30 MICROINCHES/(0.762 MICROMETERS) MINIMUM GOLD IN SELECTE AREA;  
 100 MICROINCHES/(2.54 MICROMETERS) MINIMUM TIN IN SELECTE AREA;  
 OVER NICKEL UNDERPLATE OVERALL.
  - PARTS USED IN CONJUNCTION WITH MOLEX PRODUCT SPECIFICATION #PS-71719-9999.
  - PACKAGING PER MOLEX SPECIFICATION #PK-70873-0252.
  - PARTS CONFORM TO MOLEX APPLICATION SPECIFICATION #AS-71715-9999.

.005 MAXIMUM MISMATCH (TYP) .005 MAXIMUM MISMATCH (TYP)

DETAIL "A"  
 SCALE 10X

DIMENSIONS SHOWN <input type="checkbox"/> INCH <input checked="" type="checkbox"/> METRIC		UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2°		▽ = 0 ▼ = 0 REVISE ONLY ON CAD SYSTEM		
3 PLACE ± .010 ---		INCH METRIC		TITLE .050" PITCH LFH, 50 CKT. MALE INSERT-MOLDED CONTACT STRIP, SALES DETAIL		
2 PLACE ± --- ± ---		1 PLACE --- ± ---		MOLEX INCORPORATED SHEET NO. DATE U.S.A. 1 OF 1 04/23/96		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		PART NO. 71715-4001		DRWG. NO. SDA-71715-4001		
DRWG. BY GLT		CHK'D. BY GLT		FILE NAME S7171504.DGN		
APP'D. BY CWF		SCALE 5:1		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.		
LTR.	REVISIONS	LTR.	REVISIONS	MFG.	SH.	REV.