

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
APPLICABLE STANDARD									
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO 85 °C(NOTE 1)			STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C			
	VOLTAGE	250 V AC			APPLICABLE CONNECTORS	DF1B-*(D)S-2.5R(C)			
	CURRENT	3A			OPERATING HUMIDITY RANGE	UL1061:AWG24			
<b>SPECIFICATIONS</b>									
ITEM		TEST METHOD			REQUIREMENTS			QT	AT
<b>CONSTRUCTION</b>									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			×	×
MARKING		CONFIRMED VISUALLY.						×	×
<b>ELECTRIC CHARACTERISTICS</b>									
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz)			30 mΩ MAX.			×	—
<b>MECHANICAL CHARACTERISTICS</b>									
CONTACT INSERTION AND EXTRACTION FORCES		□0.635±0.002mm BY STEEL GAUGE.			INSERTION FORCE 4.4 N MAX EXTRACTION FORCE 0.44 N MIN			×	—
MECHANICAL OPERATION		30 TIMES INSERTIONS AND EXTRACTIONS.			① CONTACT RESISTANCE: 30mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS			×	—
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75mm, AT 2 h, FOR 3 DIRECTIONS.			① NO ELECTRICAL DISCONTINUITY OF 1μs. ② CONTACT RESISTANCE: 30 mΩ MAX			×	—
SHOCK		490 m/s <sup>2</sup> DIRECTIONS OF PULSE 11 ms AT 3 TIME FOR 3 DIRECTION.			③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS			×	—
<b>ENVIRONMENTAL CHARACTERISTICS</b>									
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 →5 TO 35→85 →5 TO 35 °C TIME 30 → 10 →30 → 10 min UNDER 5 CYCLES.			① CONTACT RESISTANCE: 30 mΩ MAX ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS			×	—
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90 TO 95 %, 96 h.			① CONTACT RESISTANCE: 30 mΩ MAX ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS			×	—
REMARKS NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
Unless otherwise specified, refer to MIL-STD-1344.					W. Fukuchi '00. 4. 12	W. Fukuchi '00. 4. 12	T. Miyajima '00. 4. 12	K. Katayama '00. 4. 13	
Note QT: Qualification Test AT: Assurance Test ×:Applicable Test									
<b>HRS HIROSE ELECTRIC CO., LTD.</b>					<b>SPECIFICATION SHEET</b>			PART NO. <b>DF1B-R24F</b>	
CODE NO.(OLD) CL		DRAWING NO ELC4-020205			PEART NO CL541-0217-9			1/1	

Apr.1.2017 Copyright 2017 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

TO