

# VIP-CAB-FLK14/FR/OE/0,14/1,0M

Order No.: 2900123



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2900123>

Assembled round cable with a 14-pos. molded socket strip (90° output) and an open end. On the open end, the wires are labeled with 1 to 14 and have ferrules, cable length: 1 m

| Commercial data          |                    |
|--------------------------|--------------------|
| GTIN (EAN)               | 4046356476522      |
| sales group              | I580               |
| Pack                     | 1 pcs.             |
| Customs tariff           | 85444290           |
| Weight/Piece             | 0.0776 KG          |
| Catalog page information | Page 260 (IF-2009) |

#### Product notes

WEEE/RoHS-compliant since:  
04/01/2009



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

| Technical data                          |                  |
|---|------------------|
| <b>General</b>                          |                  |
| Nominal voltage $U_N$                   | < 50 V AC        |
|   | 60 V DC          |
| Max. current carrying capacity per path | 1 A              |
| Max. conductor resistance               | 0.16 $\Omega$ /m |

|   |   |
|---|---|
| Ambient temperature (operation)               | -20 °C ... 50 °C                                    |
| Ambient temperature (storage/transport)       | -20 °C ... 70 °C                                    |
| Number of positions                           | 14  |
| Number of positions, control side             | 14  |
| Number of connectors, control side            | 0   |
| Number of positions, module side              | 14  |
| Number of connectors, modul side              | 1   |
| Fixed cable length                            | 1 m   |
| Single wire, cross section                    | 0.14 mm <sup>2</sup>                                |
| AWG   | 26  |
| Conductor construction: Number of litz wires: | 7   |
| Single wire, material                         | Cu tin-plated                                       |
| External diameter                             | 6.4 mm  |
| Cable, preassembly                            | Insulation displacement, IEC 60352-4/DIN EN 60352-4 |
| Shielding                                     | no  |

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;