

Specification Sheet

Part Number: 596-00499



Solar Label, 2017 Code, WARNING TURN OFF PV PRIOR TO..., 4.125" x 2.0", VL, Orange/White, 50/roll

Article Number	596-00499
Type	WTOPVLBL
Color	Orange (OG)
Features & Benefits	<ul style="list-style-type: none">• Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance.• Supplied with an aggressive adhesive to ensure long life.• Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.• Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.
Quantity Per	roll

Product Description

HellermannTyton pre-printed vinyl Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, 2017 Code, WARNING TURN OFF PV PRIOR TO..., 4.125" x 2.0", VL, Orange/White, 50/roll

Global Part Name

WTOPVLBL-443/552-OG

Technical Description

Pre-Printed Solar Label, "WARNING - TURN OFF PV BEFORE WORKING..", 4.125" X 2", Orange/White

Local Order Number 2

Cross Reference = 10 per pack: 596-00664; Metal Solar Placard 5 pack: 596-00832

Length L (Imperial)

4.125

Length L (Metric)

104.6

Width W (Imperial)

4.125

Width W (Metric)

104.6

Thickness T (Metric)

64.0

Height H (Imperial)

2.0

Height H (Metric)

50.80

Material	Type 443/552, UV Stable Flexible White Vinyl with Acrylic Laminate
Material Shortcut	443/552
Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature (Metric)	-40°F to +174°F (-40°C to +79°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	NEC2017 UL 969
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1
Weight (Metric)	0.521

Weight (Imperial)

3.2