



-Protection level: IP67/65  
 - Temperature range: -40°C ...+70°C

|           |                |  |           |
|-----------|----------------|--|-----------|
| 10        | 33582113000001 | Fiber optic breakout cable MM 62.5/125 | 300       |
| 9         | 33582111000001 |  | 100       |
| 8         | 33582110600001 |  | 60        |
| 7         | 33582110500001 |  | 50        |
| 6         | 33582110400001 |  | 40        |
| 5         | 33582110200001 |  | 20        |
| 4         | 33582110100001 |  | 10        |
| 3         | 33582110050001 |  | 5         |
| 2         | 33582110030001 |  | 3         |
| 1         | 33582110010001 |  | 1         |
| Cont. No. | Part-no.       | Type of cable                          | Dim.a [m] |

|   |  |                       |                          |                             |                    |   |              |
|---|--|-----------------------|--------------------------|-----------------------------|--------------------|---|--------------|
|   | All rights reserved<br>Department EC PD - RO | Created by<br>OLESCHR | Inspected by<br>AVRAM    | Standardisation<br>HOFFMANN | Date<br>2013-05-31 | State<br>Final Release                                  | Ref.<br>Sub. |
|   | Title<br>Fiber optic cable assembly          |                       |                          |                             |                    | Doc-Key / ECM-Nr.<br>100173352/UGD/009/A<br>50000062574 |              |
| HARTING Electronics GmbH<br>D-32339 Espelkamp |  | Type<br>TB            | Number<br>3358211XXX0001 |                             | Rev.<br>A          | Page<br>1/1   |              |