

## Specification Sheet

Part Number: 151-02104



High Torque Double Mnt, 4-Way, Mounting Hole .375", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg

**Article Number**

151-02104

**Type**

HDM375BDM4W

**Color**

Black (BK)

**Features & Benefits**

- Arched H-profile surface allows for broad surface contact with the bundle, minimizing pinching and crushing of the bundles.
- High torque metal bushing allows for strength in heavy duty applications.
- These mounts contain a small tab inside the mounting hole to temporarily engage the threads which allows assemblers to pre-install the mount on a stud with a washer and nut.

**Quantity Per**

carton

**Product Description**

High Torque Double Mounts are designed for use with power assisted impact wrenches and are molded with a metal bushing to withstand the forces required to tighten grade 8 bolts. Mounts are designed for routing multiple bundles with HellermannTyton heavy duty T250, T255, and wide strap cable ties to harness wires and hoses. The bundle is secured directly over the mounting fastener. The arched saddle surface allows for a broad surface contact with the bundle, minimizing pinching and crushing of the bundles. Mounts accept all standard cable ties up to .5" wide.

**Short Description**

High Torque Double Mnt, 4-Way, Mounting Hole .375", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg

**Global Part Name**

HDM375BDM4W-PA66HIRHSUV-BK

**Length L (Imperial)**

3.50

**Length L (Metric)**

89.0

**Fixation Method**

Screw Mounting and Rivet

**Width W (Imperial)**

1.4

**Width W (Metric)**

35.6

**Height H (Imperial)**

0.99

**Height H (Metric)**

25.2

**Cable Tie Width Max (Imperial)**

0.5

**Cable Tie Width Max (Metric)**

12.7

**Mounting Hole Diameter D (Imperial)**

0.405

**Mounting Hole Diameter D (Metric)**

10.29 mm

**Mounting Hole Diameter D Max (Metric)** 10.29

**Mounting Hole Centers (Imperial)** 0.405

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Flammability** UL 94 HB

**Operating Temperature (Metric)** -40°F to +230°F (-40°C to +110°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 100

**Package Quantity (Metric)** 100

**Content Unit(BMEcat)** pcs.

**Weight (Metric)** 0.0396

**Weight (Imperial)** 0.0874

