


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 7/8-20UNEF-2A     |
| B   | 14.2              |
| C   | 3.2               |
| D   | 25.1              |
| E   | 19                |
| F   | 23                |
| G   | 30                |
| H   | 3.1               |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 5   | KONTAKTSTIFT/ CONTACT PIN           |
| 8   | DOSENGEHÄUSE / SHELL                |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

|   |
|---|
| <b>Material Specification:</b>                                  |
| Shell Material: Aluminium alloy                                 |
| Shell Plating: Olive drab chromate coating over cadmium plating |
| Insulator Material: Neoprene                                    |
| Contact Material: Copper alloy                                  |
| Contact Plating: Hard silver                                    |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
 CUSTOMER



description CA3102E14S-4P  
 Box mounting receptacle  
 Solder Cup / Pin / Layout: 14S-4