



PART NUMBER DESCRIPTION

GTLP50X6_ GRIP TIE COLOR

NOTES:

1. AVG SHEAR STRENGTH = 20 PSI
2. AVG PEEL STRENGTH = .30 LBS/IN WIDTH
3. TENSILE LOOP & MAX BUNDLE DIA ARE BASED ON 2" MIN HOOK & LOOP ENGAGEMENT

MIN LOOP TENSILE (LBS) ③	MAX BUNDLE DIA ③	LENGTH	PART NUMBER
40	1.00	6.00	GTLP50X6_
40	1.75	8.00	GTLP50X8_
40	2.63	11.00	GTLP50X11_

HellermannTyton

ALL PROPRIETARY RIGHTS IN THE SUBJECT MATTER SHOWN ON THIS DRAWING ARE EXCLUSIVE PROPERTY OF HELLERMANN TYTON

name	date	city, state

REVISION

DR level	01
AW date	01/09/04
by	AAC
ECN #	003392
part level	-

TOLERANCES

.XXXX = ±.0005
 .XXX = ±.005
 .XX = ±.01
 .X = ±.03
 ∠ = ±0.5°
 unless otherwise specified

units inches

number SEE CHART phase PRODUCTION

name GTLP50 LOW PROFILE GRIP TIES

material HOOK & LOOP

FORMAT AH version M	CAD ACAD	scale 1X
computer file number CT\CST\2007052_01	previous number	
drawn A.A.C.	checked K.A.C.	approved
09/19/02	01/09/04	
type CUSTOMER	sheet 1 of 1	
number CT2007052CST		

INVENTORS

PART

DRAWING