



Smart Technology. Delivered.

# SR2401120D Wide-Angle Coverage Directional Antenna



## 2.4-2.5 GHz, 11 dBi, 120° SECTORED AND WIDE-ANGLE COVERAGE DIRECTIONAL ANTENNA

Laird's 120° wide H-plane sectored antenna offers systems integrators an antenna for use with sectorized base stations when wide-directional pattern characteristics are preferable to omnidirectional pattern characteristics. Enclosed in an attractive UV-stable, weatherproof radome housing, the antenna satisfies indoor aesthetic requirements yet remains rugged enough to withstand outdoor exposures.

Depending on the required coverage area, one to three 120° sectored antennas can be deployed at a base station site. While a single antenna can be wall- or pole-mounted to provide directional coverage, the TM905BRK's mechanical down-tilt mount also allows a customized antenna pattern tilt. The design is electrically and mechanically robust, ensuring a lifetime of stable, trouble-free service, as well as predictable, consistent performance.

The standard antenna comes with a 12 in low-loss coax pigtail and N-female connector. Alternative coax cable lengths and connector types are also available.


### FEATURES

- Suitable for indoor or outdoor applications
- Articulating mounts available

### MARKETS

- WiMAX

PARAMETER	SPECIFICATION
Frequency Range (GHz)	2.4-2.5
Gain (dBi)	11
VSWR	1.5:1
3 dB Beamwidth - E-Plane	13°
3 dB Beamwidth - H-Plane	120°
Polarization	Linear
RF Connector (f)	N
Power (watts)	25 watts
Dimensions	3 x 23 x 2 in (7.6 x 58.4 x 5.1)
Mount Style	



SR2401120D

Americas: +1.847.839.6925  
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941  
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127  
IAS-AsiaSales@lairdtech.com

[www.lairdtech.com](http://www.lairdtech.com)

Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective by reason of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.



ANT-DS-SR2401120D 1115

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.