

F-370

1281 (7/69)

APPLICATOR PARTS LIST

TYPE

SIDEMISE

.156 Dia.
Pin & Soc.

AMP INCORPORATED
HARRISBURG, PENNA.

| NO. | DESCRIPTION | REQ. | PART NO. | NO. | DESCRIPTION | REQ. | PART NO. | |
|-----|--------------------------|------|------------|-----|--------------------------------|----------|-----------|-------|
| 1 | WIRE CRIMPER PIN | 1 | 456411-6 | 42 | Shear Plate - Left | 1 | 454206-1 | |
| 2 | INS. CRIMPER | 1 | 2-473740-1 | 43 | Shear Block - Right | 1 | 386372 | |
| 3 | ANVIL | 1 | 690386-1 | 44 | Floating Shear | 1 | 465406 | |
| 4 | ANVIL SPACER | 1 | 811780-1 | 45 | Retaining Plate - Front | 1 | 811714-3 | |
| 5 | SHEAR BLADE | | | 46 | Retaining Plate - Rear | 1 | 810822-1 | |
| 6 | REAR SHEAR PLATE | | | 47 | Spring - Shear Return | 1 | 374322 | |
| 7 | SHEAR BLADE SPACER | | | 48 | Shear - Depressor | 1 | 811946-3 | |
| 8 | FRONT SHEAR PLATE | | | 49 | Key - Shear Retainer | 1 | 386358 | |
| 9 | REAR ANVIL SPACER PLT. | | | 50 | Guard Mount | 1 | 811306-1 | |
| 10 | FRONT Strip Hold | 1 | 811593-3 | 51 | | | | |
| 11 | TOOL SPACER PIN | 1 | 387744 | 52 | | | | |
| 12 | CRIMP SPACER | 1 | 370827 | 53 | | | | |
| 13 | FRONT STRIP GUIDE | 1 | 810971-6 | 54 | Rear Strip Guide Spacer | 1 | 811527-2 | |
| 14 | REAR STRIP GUIDE | 1 | 465440-8 | 55 | Hold Down Ass'y. | 1 | 811849-1 | |
| 15 | RAM 473699 | 1 | 473699 | 56 | Holder | | 811850-1 | |
| 16 | TOOL HOLDER | | | 57 | Cover | | 811851-1 | |
| 17 | ADJ. CRIMP MOUNT Ass'y. | 1 | 465392-9 | 58 | Blade | REF | 811852-1 | |
| 18 | ADJ. BLOCK | | | 59 | Spring | | 6-22279-6 | |
| 19 | APPLICATOR MOUNT ASSY. | | | 60 | Fl. Hd. Soc. Cap. Ser. 1/2 lg. | | 1-21003-8 | |
| 20 | BASE PLATE | 1 | 465100 | 61 | | | | |
| 21 | BASE BLOCK | 1 | 465101 | 62 | WIRE CRIMPER Soc. | 1 | 453941-0 | |
| 22 | STRIP GUIDE PLATE | 1 | 465513-4 | 63 | TOOL SPACER Soc. | 1 | 470493-6 | |
| 23 | ANVIL HOLDER | | | 64 | | | | |
| 24 | Wire Stop Guide | 1 | 811787-2 | 65 | Tension Adj. Plate | 1 | 374999 | |
| 25 | STRIPPER - Wire Stop | 1 | 386361-1 | | MISCELLANEOUS | | 453594 | |
| 26 | STRIPPER MOUNT | 1 | 386362 | 66 | 2" Dia. Reel Support Ass'y | 1 | 56500-6 | |
| 27 | RETAINER PLATE | 1 | 389078 | 67 | | | | |
| 28 | STRIPPER MOUNT BRACKET | 1 | 387715-1 | 68 | | | | |
| 29 | STRIPPER BUSHING | 1 | 389049-1 | 69 | Paper Separator | 1 | 674927-1 | |
| 30 | STOCK DRAG | 1 | 386955 | 70 | | | | |
| 31 | STOCK DRAG HANDLE | | | 71 | | | | |
| 32 | STOCK DRAG STUD 374900 | 1 | 374900 | 72 | | | | |
| 33 | STOCK DRAG SPRING 370572 | 1 | 370572 | | REVISION RECORD | DATE | BY | ECN |
| 34 | STOCK DRAG ADJ. Nut | 1 | 21022-3 | A | SUPERSEDES 545793-3 | 10-16-68 | RB | L6253 |
| 35 | FEED FINGER HOLDER | 1 | 386942 | B | 32, 33 & FEED | 6-3-69 | RB | L6692 |
| 36 | FEED FINGER | 1 | 386941 | C | ITEM 10 WAS -1 42 WAS RISES | 5-20-70 | RB | L7551 |
| 37 | FEED FINGER TIP | 1 | 387251 | D | PER ECN | 9-10-70 | RB | L7774 |
| 38 | FEED FINGER Guide | 1 | 689915-2 | E | REV PER SUPP | 8-16-71 | RB | L8332 |
| 39 | BASE CASTING | 1 | 570238 | F | HARDWARE WAS 687509-1 | 1-3-72 | RB | L8659 |
| 40 | GUARD 457665-2 | 1 | 457665-2 | G | REV. PER ECN | 3-20-72 | RB | L8781 |
| 41 | Bracket Guard | 1 | 811304-1 | H | REV PER ECN | 4-2-73 | RB | L9621 |
| | | | | J | ADD ITEM 62163 | 8-23-74 | RB | R724 |
| | | | | JT | INACTIVE FRD | 2-24-77 | RB | R195 |

| CRIMPING DATA | | | | TERMINALS |
|----------------------------------|--------------|--------------|----------|-----------|
| TO APPLY TERMINAL | | | | Socket |
| WIRE SIZE | | | | Feed |
| 12 | CRIMP HEIGHT | | .087 | .660 |
| | | | | 61210 |
| 10 | CRIMP HEIGHT | | .106 | |
| CRIMP SIZE | | TYPE | FEED | |
| WIRE | .140 | F | .660 | FEED .500 |
| INSUL. | .210 | F | .500 | Pin |
| SLEEVED | | | | |
| INSULATION RANGE | | WIRE RANGE | | |
| .185 Max. | | 12 - 10 | | 61211 |
| EXPLODED VIEW | | | | |
| A-6002-4-6 | | | | |
| REMARKS: | | | | |
| Mounts on Item 13 | | | | |
| Top Tool Mounting Sequence | | | | |
| From Ram Outward: Item | | | | |
| 55, 11, 1, 12, 17 & 48. | | | | |
| 61210 USE 62 & 63 | | | | |
| 61211 USE 1 & 11 | | | | |
| INACTIVE | | | | |
| FOR REPLACEMENT ONLY | | | | |
| RECOMMEND PURCHASE REPLACEMENT | | | | |
| THIS APPLICATOR IS TO BE USED ON | | | | |
| AMP-O-LECTRIC 1-471273-3 | | | | |
| DIST. 4 | | | | |
| SERIAL NO. | | DATE SHIPPED | | DESIGNED |
| | | | | 8/10/68 |
| CUSTOMER NAME AND ADDRESS | | | | CHK'd |
| | | | | 10-21-68 |
| | | | | APP'D |
| | | | | 10/21/68 |
| APPLICATOR NUMBER | | REV. | | SHEET |
| | | K | 565793-4 | 1 of 1 |
| Use Hardware Sheet #687511-8 | | | | OK |

C

B



Handwritten signatures and dates: '10-21-68', '10/21/68', '10/21/68', '10/21/68'.