



Connector retention and insertion forces on the PCB = 25 / 80 newtons

| | | | | | | | | | | | | |
|---|----------------|-------------------|-------------------|------|-------|----------|---------|-------------------------------|--|--|--------------------------------|-------------------|
| A | 09 66 255 3533 | M3 | 1 | | | | | | <p>All Dim. in mm Orig. Size DIN A 4</p> | D-sub, High temperature, 15 poles, female, straight, with solder pins 2.9, screw lock and grounding board lock. | Maßstab/ Scale 1,5:1 | |
| | 09 66 255 6533 | M3 | 2 | | | | Detail. | 04/09/02 | | | | YT |
| | 09 66 255 7533 | M3 | 3 | | | | Insp. | | | | | |
| | 09 66 255 3513 | 4-40 UNC | 1 | | | | Stand. | | | | | |
| | 09 66 255 6513 | 4-40 UNC | 2 | | 31892 | 05/05/04 | JH | HARTING EURL F-95972 Paris | | | TB 09 66 255 x5x3 | Blatt/ Page 1/ |
| | 09 66 255 7513 | 4-40 UNC | 3 | | 31084 | 04/09/02 | YT | | | | | |
| | Part number | Screw lock thread | Performance level | Mod. | Dat. | Name | | | | Sub. | | |