

Specification Sheet

Part Number: T120R0UVC2



Heavy Duty Cable Tie, 15.2" Long, UL Rated, 120lb Tensile Strength, PA66UV, Black, 100/pkg

Article Number	111-00400
Type	T120R
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• UV stabilized heavy duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures.• Head design provides high tensile strength with very low insertion force.• Bent tail ensures a quick and simple installation.
Quantity Per	bag

Product Description

HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description

Heavy Duty Cable Tie, 15.2" Long, UL Rated, 120lb Tensile Strength, PA66UV, Black, 100/pkg

Global Part Name

T120R-PA66UV-BK

Minimum Tensile Strength (Imperial)

120.0

Minimum Tensile Strength (Metric)

535.0

Length L (Imperial)

15.2

Length L (Metric)

387.0

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.30

Width W (Metric)

7.6

Bundle Diameter Min (Imperial)

0.20

Bundle Diameter Min (Metric)

5.0

Bundle Diameter Max (Imperial)

4.1

Bundle Diameter Max (Metric)

104.1

Thickness T (Imperial)	0.07
-------------------------------	------

Thickness T (Metric)	1.8
-----------------------------	-----

Material	Polyamide 6.6 UV-resistant (PA66UV)
-----------------	-------------------------------------

Material Shortcut	PA66UV
--------------------------	--------

US MIL SPEC	MS3367-3-0
--------------------	------------

SAE-AS33671	Flammability
-------------	---------------------

UL 94 V2	Halogen free
----------	---------------------

Yes	Operating Temperature (Metric)
-----	---------------------------------------

-40°F to +185°F (-40°C to +85°C)	Reach Complaint(Article 33)
----------------------------------	------------------------------------

Yes	ROHS Complaint
-----	-----------------------

Yes	Certification/Specification WEB
-----	--

CAGE Code 53421 BACS38K UL-ZODZ2.E64139	UL Recognized (US)
---	---------------------------

Yes	UL Recognized (US and Canada)
-----	--------------------------------------

Yes	
-----	--

Package Quantity(Imperial)	100
-----------------------------------	-----

Package Quantity (Metric) 100

Customs Number 3926909987

Content Unit(BMEcat) pcs.

Weight (Metric) 5.14