



Large Incandescent Indicators

FOR MOUNTING IN 1" CLEARANCE HOLE
FOR 6 TO 32V OPERATION



G-6
DOUBLE CONTACT
BAYONET BASE


See lamp ratings
on page K.

Recognized under the component
program of Underwriters'
Laboratories Inc.
75W., 125V.


PER MIL-L-3661B

MATERIALS AND FINISHES

- Mounting Bushing: Standard—brass, black nickel finish.
- Lens Holder and Knurled Flange Ring: Brass, black nickel finish.
- Mounting Nut: Brass, white nickel finish.
- Internal-tooth Lockwasher: Phosphor bronze, white nickel finish.
- Terminals: Solder — brass, hot tinned.




379-3404-0531-203
Torpedo lens




378 SERIES
379 SERIES
380 SERIES
381 SERIES

BASE PART NUMBER

WITH SCREW-ON LENS CAPS



(LH79/1) 378-3404-01-203

CAP PART NUMBERS	COMPLETE ASSEMBLY PART NUMBERS
 <p>CONVEX LC21 51-0131-203 transparent</p>	378-3404-0131-203
 <p>TORPEDO LC22 80-0531-203 transparent</p>	379-3404-0531-203
 <p>CONVEX Mech. Dimmer LC23 209-0131-203 Complete blackout LC24 210-0131-203 Semi-blackout</p>	380-3404-0131-203 381-3404-0131-203

Order complete with lamp to be assured of receiving the indicator light and correct lamp together for immediate use.