

View on mating side

o	A	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	A
o	A	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	A
o	A	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	A

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

A = 6 standard contacts L=2
 D = 90 LMFB contacts L=2

S = 96 total number of contacts

Marking	Standard
Performance level	G2/0 = Contact area perform.level2 / Termination tin
Flux proof	no
Fixing clip	no
Dimensions	602-6043-201
Technical Data	PS-85013-0002

D	G2/0	a2-31	b2-31	c2-31
A	G2/0	a1,32	b1,32	c1,32
Contact symbol	Perform. level	Contact position number		

Dimens. 602-6043-201 ECN No. MC 1999-0160 98/12/10 Cd	REVISIONS		FOR PREVIOUS REVISIONS SEE MRI LIST	
	LTR	CD	98/12/10 Cd	
REVISE ONLY ON CAD SYSTEM		SH. REV.		
CAD/CAM PROJECT NAME		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
TITLE		96 pos. Male connector acc. DIN 41612 style R contacts arrangement		
PART NO.		85013-3299		SDA-85013-3299
DWG NO.		85013-3299		
SHEET NO.		1 OF 1		98/10/26
DATE		98/10/26		
DESIGN DIMENSION		<input type="checkbox"/> MM <input type="checkbox"/> IN.		
EQUIVALENT DIMENSION		<input type="checkbox"/> MM <input type="checkbox"/> IN.		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		3 PLACE ± .		
		2 PLACE ± .		
		1 PLACE ± .		
DRWG BY		Cc		
SIGN				
CHK'D BY		Er		
SIGN				
APP'D BY		FB		
SIGN				
SCALE				
IF TWO DIMENSIONS ARE SHOWN, THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY				