


IEEE1355 CABLING



J1	Wire color	J2
2-e	Brown	1-a
1-e	Blue	2-a
2-d	Red	1-b
1-d	Green	2-b
2-c	Black	2-c
1-c	White	1-c
2-b	Orange	1-d
1-b	Yellow	2-d
2-a	Violet	1-e
1-a	Grey	2-e
Shell	Braid	Shell

NOTES /

- 1.) MECHANICAL REQUIREMENTS
  - OPERATING TEMPERATURE = -20° TO +80°C
  - MATING CYCLES : 250, PERFORMANCE LEVEL 2 ( IEC 60512-5 )
- 2.) THE CONNECTOR COMPLIES REQUIREMENT : IEC 61076-4-107
- 3.) WHITE LABEL INFORMATION:
 

DATE CODE & LOT INFORMATION  
 HARTING P/N
- 4.) CABLE MUST BE PERFORMED HI-POT TEST AND CONTINUITY TEST

33 27 243 500 0018	5 m															
33 27 243 200 0017	2 m															
33 27 243 100 0016	1 m															
33 27 243 050 0015	0.5 m															
<i>Part-No.</i>	<i>Dim. L</i>															
All Dimensions in mm Original Size MM A 3	<table border="1"> <thead> <tr> <th colspan="2">Techn. Character.</th> <th colspan="2">Free size tolerances</th> </tr> <tr> <th>Det.</th> <th>Doc.</th> <th>Scale</th> <th rowspan="4">           Har-link male DE IEEE1355 cabling            double shielded cable assembly, **m         </th> </tr> </thead> <tbody> <tr> <td>Imp.</td> <td>J.S.</td> <td rowspan="3">/</td> </tr> <tr> <td>Stand.</td> <td></td> </tr> <tr> <td></td> <td></td> </tr> </tbody> </table>	Techn. Character.		Free size tolerances		Det.	Doc.	Scale	Har-link male DE IEEE1355 cabling double shielded cable assembly, **m	Imp.	J.S.	/	Stand.			
	Techn. Character.		Free size tolerances													
	Det.	Doc.	Scale	Har-link male DE IEEE1355 cabling double shielded cable assembly, **m												
	Imp.	J.S.	/													
Stand.																
ZHANAI HARTING LIMITED																
Mod.	<table border="1"> <tr> <td>Sub.</td> <td>TB 33 27 24x xxx 00xx</td> <td>Page</td> </tr> </table>	Sub.	TB 33 27 24x xxx 00xx	Page												
Sub.	TB 33 27 24x xxx 00xx	Page														

All rights reserved