



注記
NOTES

1. 各部の反りは0.5最大。
WARPING : 0.5 MAX.
2. サーマットNO.はNO."1"のみ表示。
CIRCUIT NO. : 1 ONLY.
3. PDR NO. 39-01-4**8

17.5	12.5	39-01-4038	5199-033	3
12.5	7.5	39-01-4028	5199-023	2
B	A	EDP. NO.	MATERIAL NO.	種数 NO. OF CKTS.
			MODEL NO.	5199-N3

REVISED EC NO. J2008-4275 DRWN:NAKURAA 2008/07/01 CHKD:T. HARUYAMA 2008/07/01 APPR:NUKITA 2008/11/19 A	DESCRIPTION GENERAL TOLERANCES (UNLESS SPECIFIED) 10 UNDER ±0.2 10 OVER 30 UNDER ±0.25 30 OVER ±0.3 ANGULAR ±3 ° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
		MM ONLY	4:1	METRIC		
		TITLE				SPOX 5/7.5 REC HSG
		DRAWN BY DATE				H. HIRAMOTO '91/8/20
		CHECKED BY DATE	M. FUKUSHIMA '91/8/22			
		APPROVED BY DATE	M. ENOMOTO '91/8/22			
		MATERIAL NO.	DOCUMENT NO.	SHEET NO.		
		SEE TABLE	SD-5199-002	1 OF 1		
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						

材料
MATERIAL
ナイロン66, UL94V-0
NYLON66, UL94V-0