

Specification Sheet

Part Number: T50L2C2UL



Standard Cable Tie, 15.35" Long, UL Rated, 50lb Tensile Strength, PA66, Red, 100/pkg

| | |
|---------------------|--|
| Article Number | 111-00522 |
| Type | T50L |
| Color | Red (RD) |
| Features & Benefits | <ul style="list-style-type: none">• Inside serrations allow for strong hold on cables and wire bundles.• Head design provides high tensile strength with very low insertion force.• Bent tail ensures a quick and simple installation. |
| Quantity Per | bag |

Product Description

T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

| | |
|--|--|
| Short Description | Standard Cable Tie, 15.35" Long, UL Rated, 50lb Tensile Strength, PA66, Red, 100/pkg |
| Global Part Name | T50L-PA66-RD |
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 225.0 |
| Length L (Imperial) | 15.35 |
| Length L (Metric) | 390.0 |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.19 |
| Width W (Metric) | 4.8 |
| Bundle Diameter Min (Imperial) | 0.06 |
| Bundle Diameter Min (Metric) | 1.5 |
| Bundle Diameter Max (Imperial) | 4.3 |
| Bundle Diameter Max (Metric) | 109.2 |

Thickness T (Metric)

1.4

Material

Polyamide 6.6 (PA66)

Material Shortcut

PA66

US MIL SPEC

SAE-AS33671

MS3367-2-2

Flammability

UL 94 V2

Halogen free

Yes

Operating Temperature (Metric)

-40°F to +185°F (-40°C to +85°C)

ROHS Complaint

Yes

Certification/Specification WEB

CAGE Code 53421 UL-ZODZ.E64139

UL Recognized (US)

Yes

UL Listed (US and Canada)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity(Imperial)

100

Package Quantity (Metric)

100

Customs Number

3926909987

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)