



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=± 0.4
X.XX=± 0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. RATING: 100mA @ 12VDC
 5. CONTACT MATERIAL: GOLD PLATED B
 6. CONTACT RESISTANCE: 200 Milli-OHM MAX.
 7. INSULATION RESISTANCE: 500VDC, 100 MEGA-OHM MIN.
 - ▲ 8. OPERATING FORCE: 250 ± 100GF
 9. MECHANICAL LIFE: 1,000,000 CYCLES
 10. OPERATING TEMP: -20°C TO +70°C
 11. LED COLORS: WHITE-WHITE
 12. TRAVEL: 4.50mm±0.20
 13. 2002/95/EC (ROHS) COMPLIANT
 14. ▲ DENOTES CRITICAL PARAMETER.

LED SPECS	UNITS	WHITE	WHITE
FORWARD CURRENT	mA	20	20
FORWARD VOLTAGE @20mA	V	3.0-3.6	3.0-3.6
LUMINOUS INTENSITY @ 20mA	mcd	500	500

B	21454	CHANGE CONTACT MATERIAL TO GOLD	5/13/14	EBP
A	19491	Release for Production	12/03/10	BMA
REV	PCR NO	DESCRIPTION	DATE	BY

E-SWITCH®

TITLE LP110A1NCSSW

SCALE	2	DATE	12/3/2010	DR	BMA	DWG	B231014	REV	B
-------	---	------	-----------	----	-----	-----	---------	-----	---

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED