

PCB terminal block - FKDSA-7,62 BK - 1934502

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

PCB terminal block, Pitch: 7.62 mm, Number of positions: 1, Connection method: Spring-cage conn., Mounting: Soldering, Color: black

Key commercial data

Packing unit	1 1
Minimum order quantity	50 1
Weight per Piece (excluding packing)	3.04 GRM
Custom tariff number	85369010
Country of origin	Poland

Technical data

Dimensions

Pitch	7.62 mm
Pin dimensions	0,5 x 1,0 mm
Pin spacing	7.62 mm
Hole diameter	1.3 mm

General

Range of articles	FKDS(A)
Rated surge voltage (III/3)	6 V
Nominal cross section	1.5 mm ²
Maximum load current	17.5 A
Insulating material	PA
Solder pin surface	Sn
Inflammability class according to UL 94	V2
Stripping length	11 mm
Number of positions	1

Connection data

Minimum AWG according to UL/CUL	22
Maximum AWG according to UL/CUL	12

PCB terminal block - FKDSA-7,62 BK - 1934502

Classifications

eCl@ss

eCl@ss 4.0	27141109
eCl@ss 4.1	27141109
eCl@ss 5.0	27141190
eCl@ss 5.1	27141190
eCl@ss 6.0	27261101

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002643

UNSPSC

UNSPSC 6.01	30211801
UNSPSC 7.0901	39121432
UNSPSC 11	39121432
UNSPSC 12.01	39121432
UNSPSC 13.2	39121432

Approvals

Approvals


Approvals

CSA / UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

CSA 	
mm ² /AWG/kcmil	16
Nominal current I _N	10 A

PCB terminal block - FKDSA-7,62 BK - 1934502

Approvals

Nominal voltage UN	300 V
--------------------	-------

UL Recognized

	B	D
mm ² /AWG/kcmil	22-12	22-12
Nominal current IN	10 A	10 A
Nominal voltage UN	300 V	300 V

cUL Recognized

	B	D
mm ² /AWG/kcmil	22-12	22-12
Nominal current IN	10 A	10 A
Nominal voltage UN	300 V	300 V

cULus Recognized

Accessories

Accessories

Labeled terminal marker

Marker cards - SK 7,62/5:FORTL.ZAHLEN - 0804552



Marker cards, Card, white, labeled, Horizontal: Consecutive numbers 1 - 10, 11 - 20, etc. up to 91 - 100, Mounting type: Adhesive, For terminal block width: 7.62 mm

Marker pen

PCB terminal block - FKDSA-7,62 BK - 1934502

Accessories

Marker pen - B-STIFT - 1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

Screwdriver tools

Screwdriver - SZF 1-0,6X3,5 - 1204517



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

Terminal marking

Marker cards - SK U/5,0 WH:UNBEDRUCKT - 0803922



Marker cards, Sheet, white, Unlabeled, Can be labeled with: Plotter, Office printing systems, Mounting type: Adhesive, Lettering field: 186 x 5 mm

PCB terminal block - FKDSA1-7,62 - 1790607

PCB terminal block, Pitch: 7.62 mm, Number of positions: 1, Connection method: Spring-cage conn., Color: green
