

HL 2020 E

NEW!

Available October 2016

Technical Specifications

| | |
|--------------------|--|
| Voltage: | 120 VAC / 60Hz |
| Output: | 1600 watts |
| Amps: | 13.3 |
| Temperature: | 120 – 1150 °F (50 – 620 °C) |
| Airflow rate: | 4 / 4-8 / 6-13 cfm. |
| Stages: | 3 |
| Highlights: | Higher durability (+20 %), optimized weight balance, LCD-Display, heat build-up warning, hanging ring, easily replaceable power cord, residual heat indicator, optional temperature scanner and fine dust filter |
| Power cord: | Industrial grade rubber, length: 6ft |
| Motor: | Brush motor |
| Heating element: | Ceramic heating element |
| Motor lifetime: | 600h |
| Accessories: | Use of our standard accessories |
| Dimensions: | 9.96" x 3.37" x 7.87" (l x w x h) |
| Net Weight: | 2.19 lbs (35.10 oz) |
| Single Sell Pack: | Dimensions: 10.20" x 3.54" x 9.33" Weight: 2.60 lbs (41.66 oz) |
| Country of origin: | Romania |
| Warranty: | One year limited |



| | |
|--------------|-----------|
| UPC-Code | Prod. No. |
| 018139375500 | 110025597 |



RoHS
Compliant



double insulated

ISO
9001:
2015
14001:
2015