



#### General ordering data

Order No.	1791150000
Part designation	ZDK 1.5PE
Version	Earth terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, green/yellow, TS 35
EAN	4032248239092
Qty.	100 pc(s).

#### Product notes

Product description	Z-series standard ranges provide solutions for conductor cross-sections from 0.05 to 35 mm <sup>2</sup> .
---------------------	---

#### PT OKIECEEx/ATEX rating data

Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

#### Additional technical data

Colour of insulating material	green/yellow
Connection direction	top
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	Yes
No. of identical terminals	1
No. of levels	2
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 120 °C
Product family	Z-series
Type of connection	Clamped
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	PE terminal

**CSA rating data**

Min. cross-section (CSA)	AWG 26
Max. cross-section (CSA)	AWG 16

**Conductors for clamping (additional connection)**

Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228 pt 1)	1.5 mm <sup>2</sup>

**Conductors for clamping (rated connection)**

Clamping range, min.	0.05 mm <sup>2</sup>
Clamping range, max.	1.5 mm <sup>2</sup>
Type of connection	Tension clamp connection
2nd type of connection	clamped
Connection direction	top
No. of connections	4
Stripping length	10 mm
Blade size	0.4 x 2.0 mm
Gauge to IEC 60947-1	B1
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	1.5 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>
Flexible, max.	1.5 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	1.5 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	1.5 mm <sup>2</sup>
Twin wire-end ferrule, min.	0.5 mm <sup>2</sup>
Twin wire end ferrule, max.	0.75 mm <sup>2</sup>
AWG conductor size, min.	AWG 30
AWG conductor size, max.	AWG 16
AWG conductor size, min.	0.05 mm <sup>2</sup>
AWG conductor size, max.	1.31 mm <sup>2</sup>

**Dimensions**

Width	3.5 mm
Height of lowest version	50 mm
Length	75.5 mm
TS 35 offset	42 mm

**PE rating data**

PEN function	No
Pollution severity	3
Rated cross-section	1.5 mm <sup>2</sup>
Rated impulse withstand voltage to adjacent terminal	6 kV
Rated short-time current	180 A (1,5 mm <sup>2</sup> )
Rated voltage for adjacent terminal	500 V
Standards	IEC 60947-7-2

#### UL rating data

Min. cross-section (UL)	AWG 30
Max. cross-section (UL)	AWG 16

#### Approvals

Approvals institutes



#### Downloads

STEP	1791150000_31928_ZDK_1.5PE_STP.stp
------	------------------------------------

#### Classifications

eClass 4.1	27-14-03-05
eClass 5.0	27-14-03-05
eClass 5.1	27-14-03-05

#### Similar products

Order No.	Part designation	Version
1775510000	ZPE 1.5	Earth terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, green, TS 35
1775560000	ZPE 1.5/3AN	Earth terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, green/yellow, TS 35
1775620000	ZPE 1.5/4AN	Earth terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, green/yellow, TS 35