

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	18JUN2015	DL	CW

104
27
4-M3
(93.1)

4- \varnothing 4.4
130
32
108
35

PANNEL CUT OUT

135.7
29.8
142.2
(88.4)

45.7

32
130
4- \varnothing 4.4



NOTES:

1. TECHNICAL CHARACTERISTICS:
 BODY MATERIAL: DIE CAST ALUMINIUM ALLOY
 SURFACE TREATMENT: POWDER-COATED, GRAY
 OPERATION TEMPERATURE: -40-+125°C
 DEGREE OF PROTECTION: IP65 (MATED)

注释:

1. 技术参数:
 主体材料: 铝合金
 表面处理: 粉末喷涂, 灰色
 工作温度: -40-+125°C
 防护等级: IP65(配合)

T1510243000-000	H24B-AD-LB
ASSEMBLY PART NUMBER	ASSEMBLY PART DESCRIPTION

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	18JUN2015	 TE Connectivity	
DIMENSIONS:		DAVID LI	18JUN2015		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		CHK	18JUN2015		
mm		CHRIS WANG	18JUN2015		
		APVD	18JUN2015	NAME	H24B-AD-LB
0 PLC ±-		PRODUCT SPEC		108-137013	
1 PLC ±-		APPLICATION SPEC		114-137013	
2 PLC ±-		WEIGHT		-	
3 PLC ±-		SIZE		A3	
4 PLC ±-		CAGE CODE		-	
ANGLES ±-		DRAWING NO		©-T1510243000000	RESTRICTED TO
FINISH		CUSTOMER DRAWING		SCALE	1:2
-		SHEET		1	OF
-		REV		A	

1470-19 (3/13)