



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERMINAL NUMBERS FOR REF ONLY
 4. RATING: CURRENT: .01mA-250mA
VOLTAGE: 20mV-50 VDC
 5. OPERATING LIFE: 30,000 MAKE-AND-BREAK CYCLES
 6. INSULATION RESISTANCE: 1000VDC, 1000M OHM. MIN.
 - ▲ 7. OPERATING FORCE: 250gf ± 100 GRAMS
 8. OPERATING TEMP.: -30°C to 85°C (B)
 - ▲ 9. TRAVEL: MOMENTARY
FULL TRAVEL 5.1 ± 0.5mm
 10. CONTACT RESISTANCE: 50 m OHM. MAX.
 11. ▲ DENOTES CRITICAL PARAMETER.
 12. 2002/95/EC (ROHS) COMPLIANT
 - ▲ 13. LED COLOR: GREEN

▲ LED SPECS	UNITS	GREEN
FORWARD CURRENT	mA	20
FORWARD VOLTAGE @20mA	V	2.2 TYP-2.6 MAX
LUMINOUS INTENSITY @ 20mA	MCD	50



B	19585	CHANGE DIMS & TEMP.	1/14/11	BGL
A	18803	New Release	1/19/10	rc
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE LP370ACGG				
SCALE	DATE	DR	DWG	REV
2=1	1/20/2010	rc	T010001	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED