



2400-2485 MHz VERTICALLY POLARIZED SECTOR ANTENNAS

The vertically polarized sector antenna systems offered by Laird are constructed of UV stable fiberglass radomes for extremely long service life in the most demanding conditions. The antennas are constructed using corrosion resistant metal elements and a unique air dielectric system which are more stable than PCB based antenna systems because they don't absorb moisture, which can degrade the performance of PCB based antenna systems. The 14 dB sectors come with a stainless steel scissor bracket system for ease of installation and alignment. The 9 dBi sector comes with a galvanized steel bracket with stainless steel hardware.

FEATURES

- Vertically polarized
- 90°, 120° and 180° models with gains from 9 dBi to 14 dBi
- Type N female integrated connector
- Extremely rugged for long service life in extreme environments
- Weatherproof

MARKETS

- 2.4 GHz ISM band applications
- 802.11b and 802.11g wireless systems
- WiFi base station antennas
- Point-to-multi-point systems
- Wireless internet
- WiMAX


PARAMETER	SA24-90-9	SA24-120-9	SA24-180-14
Frequency range	2400 - 2485 MHz	2400 - 2485 MHz	2400 - 2485 MHz
Input return loss (S11)	-14 dB	-14 dB	-14 dB
VSWR	1.5:1	1.5:1	1.5:1
Impedance	50 ohm	50 ohm	50 ohm
Input power	100 W	100 W	100 W
Pole diameter (OD)	1 - 2 in (25-50 mm)	1 - 2 in (25-50 mm)	1 - 2 in (25-50 mm)
Operating temperature	-40 to +70°C	-40 to +70°C	-40 to +70°C
Gain	9.5 dBi	9 dBi	14 dBi
Horizontal beamwidth	90°	120°	180°
Vertical beamwidth	30°	30°	10°
Front-to-back	25 dB	25 dB	25 dB
Down tilt (mechanical)	45°	45°	10°
Weight (with bracket)	25 oz (0.7 kg)	25 oz (0.7 kg)	11 lbs (5 kg)
Dimensions (L x W x H)	10 x 6.5 x 2.5 in (254 x 165 x 63.5 mm)	10 x 6.5 x 2.5 in (254 x 165 x 63.5 mm)	40 x 10.25 x 7 in (1020 x 260 x 180 mm)

WIND LOADING


MODEL	SQ. IN	100 MPH	125 MPH	100 MPH 1/2 IN RADIAL ICE
SA24-xx-9	65	16.3 lb	25.4 lb	17 lb
SA24-180-9	400	100 lb	156 lb	102 lb

SYSTEM ORDERING


SA24-90-9	9 dBi 90° 2.4 GHz VPOL sector antenna
SA24-120-9	9 dBi 120° 2.4 GHz VPOL sector antenna
SA24-180-14	14 dBi 180° 2.4 GHz VPOL sector antenna



SA24-90-9



SA24-120-9



SA24-180-14

Americas: +1.847.839.6925
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-SA24 0617

Any information furnished by Laird and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2017 Laird. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.