

CT-200 – Universal Compression Tool - Data Sheet

This tool is designed for use on F Connectors (RG59, RG6, & RG11), BNC Connectors (RG59 & RG6) and RCA Connectors (RG59 & RG6). Tool is designed with a dual head and adjustment dial for each unique connector application. BNC connectors must be over 1.5” in length.

COMPATIBLE CONNECTORS:

PPC: CMP6, CMP6Q, CMP59Q, CMP11, EX6XL, EX59XL, EX59XLHE, EX6XLW9, EX6LP, EX7, EX7N716, EX11, EX11N716, EX320QR, EX320N716, EX6/59, EX6W8, EX59HE, EX6P, EX11N716PLPLUS, CMPRCA6, EXBNC6, EXBNC9167

T & B (Belden) - Snap -n-Seal - SNS1P6RMBL, SNS1P6RMBK, SNS1P6RMY, SNS1P6RMR, SNS1P6RMW, SNS1P6RMG

Digicon - DS6, DS59, DS59Q, DS11, DS7

Corning Gilbert UE: GF-UE-59, GF-UE-59Q, GF-UE-6, GF-UE-6Q, GF-UE-5.1, RCA-UE, BNC-UE, G-BNCF-FM, GA-BNC-UR-59 HEC, GF-UR-6, GF-UR-59, GAF-UR-11 MH, GF-URS-59

Times Fiber Communications: TFC-QC2-06-3, TFC-QC2-06Q-3, TFC-QC2-06U-3, TFC-QC2K-06-3, TFC-QC2T-06Q-3, TFC-QC2T-06U-3, TFC-QC2Q5-06U-3, TFC-QC2-59-3, TFC-QC2-59Q-3, TFC-QC2K-59-3, TFC-QC2K-59Q-3, TFC-QC2H-59-3, TFC-QC2-11U-3

Plus many other brands and styles including F, RCA & BNC Types.



Specifications	
Connector Type	F Short, F Long, BNC, RCA
Features	U-Shaped Handle, Dual Head and Adjustment
Length	6-3/4” (171mm)
Weight	1.026 lbs
UPC No.	811490012035