


Printed-circuit board connector - SMC 1,5/ 6-G-3,81 HT BK-R44 - 1958672

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Header, Number of positions: 6, Pitch: 3.81 mm, Color: Black, Contact surface: Tin

Key commercial data

Packing unit	1 PCE
Minimum order quantity	160 PCE
GTIN	 4 017918 920456
Custom tariff number	85366990
Country of origin	GERMANY

Technical data

Dimensions

Pitch	3.81 mm
-------	---------

General

Range of articles	SMC 1,5/..-G-HT
Color	Black
Number of positions	6

Classifications

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002637
ETIM 5.0	EC002637

UNSPSC

UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409
UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409

Printed-circuit board connector - SMC 1,5/ 6-G-3,81 HT BK-R44 - 1958672

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402

Approvals

Approvals

Approvals

GOST / UL Recognized / cUL Recognized / UL Recognized / GOST / cULus Recognized

Ex Approvals

Approvals submitted


Approval details


GOST

UL Recognized		
	B	D
Nominal current I _N	8 A	8 A
Nominal voltage U _N	300 V	300 V

Printed-circuit board connector - SMC 1,5/ 6-G-3,81 HT BK-R44 - 1958672

Approvals

cUL Recognized 		
	B	D
Nominal current I _N	8 A	8 A
Nominal voltage U _N	300 V	300 V

UL Recognized 		
	B	D
Nominal current I _N	8 A	8 A
Nominal voltage U _N	300 V	300 V

GOST 		
---	--	--

cULus Recognized 		
--	--	--